



HYDRA mate

HYDRAMATE STANDARD HOUSINGS

STANDARD CARTRIDGE HOUSINGS FEATURE
UNIQUE AND INNOVATIVE DESIGN.



APPLICATIONS

- Commercial
- Industrial
- Residential

FEATURES

- Reinforced polypropylene housings have excellent chemical resistance
- Buttress threads and uniform walls for easier cartridge change and improved strength
- Optional pressure-relief/bleed button
- Leak-proof sealing with top-seated floating Buna-N o-ring
- Equipped with 3/4" NPT inlet and outlet ports
- Accommodate a wide range of 2-1/4" to 3-1/8" diameter cartridges
- Accepts standard DOE cartridges

SPECIFICATIONS

Construction	Available in 10" and 20" sizes in clear and opaque
Material	Durable polypropylene or FDA-compliant, clear styrene-Acrylonitrile (SAN)
Cup	Reinforced Polypropylene
Button Assembly	300-series Stainless Steel, EPDM, and Polypropylene
O-Ring	Buna-N
Maximum Temperature	120°F (51.7 °C)
Maximum Pressure	125Psi (8.62 bar)



@innovatekasia

INNOVATEK (ASIA) COMPANY LIMITED

95 Soi Ramintra 117, Ramintra Road, MinBuri, MinBuri, Bangkok 10510

☎ (662) 518-0745 🌐 Innovatekasia.com 📌 @Innovatekasia 📞 @Innovatekasia